

FORSF
 11.3/25.1v)
 03/01/88

MATERIAL SAFETY DATA SHEET

Company RELIANCE STEEL & ALUMINUM CO. 2550 EAST 25TH STREET LOS ANGELES, CALIFORNIA 90058	Issue Date NOVEMBER 25, 1985 REVISED MARCH 1, 1988	Identification Number SILICON BRONZE LEADED BRONZE ALUMINUM BRONZE
Trade Name (Common Name or Synonym) BRONZE	Emergency Phone Number 213-582-2272 OR YOUR LOCAL RELIANCE DISTRIBUTOR	
Chemical Name	Formula	DOT Identification Number NA

I. INGREDIENTS

NOTE: PRODUCTS UNDER NORMAL CONDITIONS DO NOT REPRESENT AN INHALATION, INGESTION OR CONTACT HEALTH HAZARD.					
BASE METAL, ALLOYING ELEMENTS AND METALLIC COATINGS	CAS #	% COMPOSITION BY WEIGHT (1)	OSHA PEL	ACGIH TLV (mg/m³) (2)	
Base Metal	CAS #		OSHA PEL		
Copper (Cu)	7440-50-8	70-99	1	1 (Dust & Mist)	
Alloying Elements					
Nickel (Ni)	7440-02-0	0-14	1	1	
Aluminum (Al)	7429-90-5	0-14	N.E.	10	
Iron (Fe)	7439-89-6	<5	10	5 (As Iron Oxide)	
Silicon (Si)	7740-21-3	<4	15	10 (Total Dust)	
Manganese (Mn)	7439-96-5	<4	5	5 (As Dust-Ceiling)	
Cobalt (Co)	7440-48-4	<2	.1	.1	
Tin (Sn)	7440-31-5	<1	2	2	
Zinc (Zn)	7440-66-6	<1	N.E.	5 (As Fume)	
Leaded Alloys					
Lead (Pb)	7439-92-1	<1	.05	.15 (Dust & Fume)	

(1) % OF ALLOYING MATERIAL VARIES WITH GRADE OF MATERIAL

(2) 1985 - 1986 ACGIH THRESHOLD LIMIT VALUE

II. PHYSICAL DATA

Material is (At Normal Conditions): <input type="checkbox"/> Liquid <input checked="" type="checkbox"/> Solid <input type="checkbox"/> Gas <input type="checkbox"/> Other		Appearance and Odor RED/GOLD METALLIC, ODORLESS	
Acidity/Alkalinity pH - NA	Melting Point > 1700 F Boiling Point NA F	Specific Gravity (H₂O = 1) > 7 Solubility in water (% by weight) NA	Vapor Pressure (mm Hg at 20 C) NA

III. PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection NIOSH/MSHA APPROVED DUST & FUME RESPIRATOR SHOULD BE USED TO AVOID EXCESSIVE INHALATION OF PARTICULATES WHEN EXPOSURE EXCEEDS TLV'S	Hands, Arms and Body. PROTECTIVE GLOVES ARE RECOMMENDED DURING HANDLING OF FINES EXPOSURE
Eyes and Face SAFETY GLASSES OR GOGGLES SHOULD BE UTILIZED AS REQUIRED BY EXPOSURE	Other Clothing and Equipment OTHER PROTECTIVE EQUIPMENT SHOULD BE UTILIZED AS REQUIRED BY THE WELDING STANDARD

IV. EMERGENCY MEDICAL PROCEDURES

IF EXPOSED TO EXCESSIVE LEVELS OF METAL FUMES, REMOVE TO FRESH AIR.
 SEEK MEDICAL AID IMMEDIATELY.
 EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES.

USEPA SF



1265405

V. HEALTH/SAFETY INFORMATION

STEEL PRODUCTS IN THE NATURAL STATE DO NOT PRESENT AN INHALATION, INGESTION OR CONTACT HAZARD. HOWEVER, OPERATIONS SUCH AS BURNING, WELDING, SAWING, BRAZING AND GRINDING MAY RELEASE FUMES AND/OR DUSTS WHICH MAY PRESENT HEALTH HAZARDS IF TLV'S ARE EXCEEDED

MAJOR EXPOSURE HAZARD

☒ INHALATION ☐ SKIN CONTACT ☐ SKIN ABSORPTION ☐ INGESTION

Short term exposure to fumes/dust may produce irritation of eyes and respiratory system. Inhalation of high concentrations of freshly formed oxide fumes of copper and lead may cause metal fume fever characterized by a metallic taste in the mouth, dryness of the throat and influenza-like symptoms.

Inhalation or ingestion of lead particles may result in lead-induced systemic toxicity. Symptoms of lead poisoning include abdominal cramps; anemia, muscle weakness and headache. Prolonged exposure can cause behavioral changes, kidney damage, CNS damage, and reproductive effects.

Nickel is listed in the 3rd Annual Report on carcinogens as prepared by the National Toxicology Program (NTP). Exposure to high concentrations of dust and fumes can cause sensitization dermatitis, inflammation and/or ulceration of upper respiratory tract and possibly cancer of nasal passages and lungs.

Recent epidemiological studies of workers melting and working alloys containing nickel/chromium have found no increased risk of cancer.

SUSPECTED CANCER AGENT? NO. THIS PRODUCTS INGREDIENTS ARE NOT FOUND IN THE LISTS BELOW
☒ YES FEDERAL OSHA ☒ NTP IARC

Fire and Explosion	Flash Point NA F	Auto Ignition Temperature NA F	Flammable Limits in Air Lower % Upper NA %	Extinguishing Media NA
	Fire and Explosion Hazards DUST HAZARD EXISTS UNDER FAVORING CONDITIONS OF SMALL PRACTICE SIZE. DISPERSION IN AIR AND STRONG IGNITION SOURCE MAY RESULT IN AN EXPLOSION			Extinguishing Media not to be used NA
Reactivity	Stability <input checked="" type="checkbox"/> Stable <input type="checkbox"/> Unstable	Incompatibility (Materials to Avoid) MERCURY, AMMONIA, ACETYLENE, ACIDS		
	Conditions to Avoid EXPOSURE DURING STORAGE TO STRONG ACIDS, BASES OR OXIDIZING AGENTS			
	Hazardous Decomposition Products TOXIC GASES, AEROSOLS & VAPORS MAY BE RELEASED IN A FIRE INVOLVING COPPER ALLOYS IF FUMES OF OTHER COMPOUNDS OR CONTACTING MATERIALS ARE INVOLVED			

VI. ENVIRONMENTAL

Spill or Leak Procedures	NA
Waste Disposal Method	ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS

VII. ADDITIONAL INFORMATION

VENTILATION: LOCAL EXHAUST VENTILATION SHOULD BE UTILIZED WHEN WELDING, BURNING, SAWING, BRAZING, GRINDING OR MACHINING WHEN EXPOSURE EXCEEDS TLV'S
 IN WELDING, PRECAUTIONS SHOULD BE TAKEN FOR AIRBORNE CONTAMINATES WHICH MAY ORIGINATE FROM COMPONENTS OF WELDING ROD
 ARC OR SPARK GENERATED WHEN WELDING OR BURNING COULD BE A SOURCE OF IGNITION FOR COMBUSTABLE AND FLAMMABLE MATERIALS

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any representation or warranty, express or implied regarding the accuracy or correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.